



# Apex Pro America, LLC

Tape. Film. Overlamination. PET.

## #AP19NR

# Premium Grade 1.9 mil Natural Rubber Solvent Based Box Sealing Tape

### APEX 1.9 mil Natural Rubber based OPP tape for medium weight box sealing application

Backing Biaxially Oriented Polypropylene Film

Adhesive Natural Rubber Solvent Adhesive

	Imperial Units	Metric Units
Total Thickness	1.90 mil	0.048mm
Film Thickness	1.10 mil	0.028mm
Adhesive Thickness	0.80 mil	0.020mm
Adhesion to Steel	22 oz/in	0.59 Kg / 24mm
Tensile Strength	19.84 LB/in	8.50 Kg / 24mm
Tack	2.09 in	5.3 cm
Holding Power	2880 minutes, 73°F	2880 minutes, 23°C
Elongation	≤170 %	
Temperature Range	Operating Temperature	Application Temperature
	32° F ~ 176° F (0° C ~ 80° C)	41° F ~ 104° F (5° C ~ 40° C)
Storage Condition:	Store in a clean,dry place. 40% relative humidity and 41°~77°F(5°~25°C) are recommended Six months shelf life from the date of dispatch if kept at the above recommended condition	

#### Important Notice:

The above properties are approximate and should only provide references and be considered typical only. The accuracy and completeness are not guaranteed. User shall determine suitability of the product for its intended use and user assumes all risk and liability whatsoever in connection therewith. The seller limits its obligation to replacement or at its option, reimbursement of the purchase price of products shown to the seller's satisfaction to have been defective at the time the seller sold it.