

#MK-560 Multipurpose Masking Tape

APEX #MK-560 is a multipurpose masking Tape for all masking jobs in the building and construction sites, industrial and car body repair applications. Temperature resitance up to 176°F/80° C for 30 minutes. Recommended to remove within 48 hours.

Features	Benefits		
Natural rubber and resins solvent based adhesive	✓ Easy removal, residue free, if removed as soon as paint is dry	 ✓ Excellent adhesion even on irregular surfaces ✓ Heat resistant up to 176°F/80°C for 30 minutes 	
Saturated crepe paper backing	 ✓ Good conformability to most surfaces ✓ Compatible with most common paints and lacquers 	√ Removable without breaking √ Hand tearable	

	Imperial Units	Metric Units	Test Method	
Total Thickness	4.92 mil	0.125 mm	PSTC - 133	
Adhesion to Steel	15.47 oz/in	0.43 kg/25mm	PSTC - 101	
Tensile Strength	19.1 lbs/in	8.66 kg/25mm	PSTC - 131	
Backing	58 g/m2 natural saturated crepe paper			
Adhesive	Natural rubber and resins solvent based			
Color	Natural			
Elongation	7.5%		PSTC - 131	
Temperature resistant	176° F (30 minutes)	80° C (30 minutes)		
Storage Condition:	Store in a clean,dry place. 40% relative humidity and 41°~77°F(5°~25°C) are recommended Six months shelf life from the date of dispatch if kept at the above recommended condition			

Important Notice:

The above propertities are approximate and should only provide references and be considered typical only. The accuracy and completeness are not guaranteed. User shall determine suitability of the product for its intended use and user assumes all risk and liability whatsoever in connection therewith. The seller limits its obligation to replacement or at its option, reimbursement of the purchase price of products shown to the seller's satisfaction to have been defective at the time the seller sold it.

562-271-7026 • WWW.APEXPRO.US